Type 1 Storm Water Pollution Prevention Plan

Project Name: Depot Dr. AK Railroad Relo of OH MOA Permit Number						
Single Family/Duplex of CommercialArea of Disturbance (sq. ft) 5,000 Excavation Depth ft): 4-5						
$\textbf{Subdivision:} \underline{ DOWNTOWN \ EDGE } \underline{ \textbf{Lot:} \textbf{Block:} \textbf{Tract:} \textbf{Parcel:} \underline{ 00102111000}$						
Street Address: 761 W 2ND AVE						
Contact Name: Annie Collie, Midnight Sun Environmental, LLC Phone Number: 907-344-3244						
The Minimum Requirements that may apply to any proposed new development or redevelopment are identified here and, if applicable, satisfied through the submission of this completed form.						
Applicability: A Type 1 SWPPP must be submitted if your project is within the MOA and if it:						

- Disturbs less than 10,000 square feet of land AND
- Is not part of a larger common plan of development. "Common Plan of Development" is a contiguous
 construction project where multiple separate and distinct construction activities may be taking place at
 different times on different schedules but under one plan. Included in this definition are most
 subdivisions and industrial parks

In particular, the operators of these projects must:

- Complete and submit this form to the MOA.
 - ✓ Fill in appropriate boxes on pages 2-4
 - ✓ Complete the site plan sketch on page 5.
 - ✓ Complete the Owner's statement on page 6.
- Complete and submit a Stormwater Runoff Threat Assessment From (Appendix A).
- Conduct work in a "good housekeeping" manner.
- Implement appropriate BMPs for control of stormwater runoff during construction, including:
 - ✓ Isolate construction materials from rainfall and snowfall events
 - ✓ Prevent the transport of sediment beyond site boundaries
 - ✓ Stabilize soll on non-building site areas
- Perform inspections and properly maintain erosion and sediment controls
- Achieve final site stabilization

Type 1 Storm Water Pollution Prevention Plan

Checkappropriate blanks below and complete the site diagram with necessary information.

Site Characteristics

		Site Characteristics
Complete	Not Applicable	
X		North arrow and site boundary, indicate and name adjacent streets or roadways.
X		Location of existing drainage ways, streams, rivers, lakes, wetlands, or wells near the site.
X		Location of existing and planned storm sewer inlets and culvert crossings within 100 feet of the site.
X		Location of existing and proposed buildings and paved areas.
X		Areas of land disturbance, which includes areas of soil disturbance for any purpose, including footings, foundations, parking, driveways, staging, temporary access, on-site wastewater systems, and on- and off-site utilities
X		Limits and approximate dimensions of the proposed disturbed area on the site.
X		Approximate gradient and direction of slopes before grading operations
X		Approximate gradient and direction of planned slopes after grading operations.
X		Overland runoff (sheet flow) coming onto the site from adjacent areas.
		Erosion Control Practices
Complete	Not Applicable	ē
 -	X	Location of temporary soil storage piles. Note: Soil storage piles should be piaced behind a silt fence, 25-foot (minimum) wide vegetative strlp, or be covered with a tarp and located more than 25 feet from any down slope road or drainage way.
N. 11 . 10	X	Location of temporary gravel access drive(s). Note: Gravel drives shall have 2 to 3 inch aggregate stone laid at least 10 feet wide and 6 inches thick. Drives shall extend from the roadway 50 feet or to the building (whichever is less).
	X	Location of sediment controls (fliter fabric fence, rock sediment trap, 25-foot wide vegetative buffer strip or other planned practices) that prevent eroded soil from leaving the site.

Note: Sediment controls should be installed along the downslope sides of the disturbed areas. Sediment Controls will be installed around soil storage piles,

Page 2 of 6

Type 1 Storm Water Pollution Prevention Plan

around inlets, at outlets of drainageways, and along adjacent drainageways which receive runoff from the site.

X		Location of sediment barriers around storm sewer inlets.
	X	
E E		Location of diversions. Note: Concentrated flow (drainageways, ditches, channels) shall be diverted (redirected) around disturbed areas. Overland runoff (sheet flow) from adjacent areas greater than 10,000 sq. ft. shall also be diverted around disturbed areas in manner that will not adversely impact adjacent landowners. 2) Diversions will be stabilized with seeding and mulching within 24 hours of diversion completion.
	X	Location of practices that will control erosion in areas of concentrated flow.
	X	Location of practices that will be applied to control erosion on steep slopes (greater than 12% grade)
		Note: Drainage ways will be stabilized with seeding, mulching, erosion control mats, in-channel fabric, or rock riprap. When used, a given in-channel barrier should not receive drainage from more than two acres of unpaved area, or one acre of paved area. In-channel practices should not be installed in perennial stream. Stabilization and other appropriate measures should be completed within 24 hours of drainageway completion. Sediment controls will be installed at the outlet ends of drainageways.
		Management Strategies
Completed	Not Applicable	*
	X	Temporary stabilization of disturbed areas.
		Note: Disturbed areas and soll piles left inactive for more than 14 days must be stabilized by seeding (between May 1 and September 1) or by other cover, such as a tarp or heavy mulching.
	X	Permanent stabilization of site by re-vegetation, lawn establishment, or other means as soon as possible.
		Indicate re-vegetation method: Seed Sod Other X
		Expected date of permanent re-vegetationAsphalt
		Revegetation the responsibility of: Builder Owner/Buyer

Page 3 of 6

Type 1 Storm Water Pollution Prevention Plan

	Planned temporary stabilization If site is not seeded by September 1 or sodded by September 15?
 X	Use of downspout to direct runoff away from structures and onto sod or pavement until vegetation is stable. After grass is well established, downspouts shall be permanently directed to grass areas.
 X	Trapping sediment during site dewatering operations. Location;
	Note: SedIment laden discharge should be temporarily ponded behind a sedIment barrier until most of the sediment settles out. If dewatering is anticipated, a dewatering plan must be submitted with this checklist.
 X	Proper disposal of building material waste so that pollutants and debris do not are not carried off-site by wind or water.

Inspection Requirements

Site operator must inspect disturbed areas, areas used for storage of materials that are exposed to precipitation, physical controls, and vehicle exits at a minimum every 14 days from March until freeze-up. Inspections must also be conducted throughout the year within 24 hours after events that produce runoff or during runoff events that last more than 24 hours.

Maintenance Requirements

If inspections reveal erosion and sediment control practices that are not effective, or appear likely to be ineffective for anticipated conditions (due to anticipated site activities and weather), the practices must be adjusted (including repair, modification, replacement, sediment removal, or additional practices) as soon as practicable, but no later than 7 calendar days following the inspection.

Final Stabilization Requirements

At the completion of land disturbing activities, all disturbed and exposed soil shall be stabilized. Areas that are uphill of installed ESC practices shall be stabilized prior to removal of those controls.

Type 1 Storm Water Pollution Prevention Plan

Instructions: Complete this diagram. Give consideration to potential erosion that may occur before, during, and after grading. Water runoff patterns can change significantly as a site is reshaped. Use additional sheets of paper if needed. Site plan should show stabilized construction exits, silt fencing, sediment trap (if necessary), areas to be stabilized, and method of stabilization.

Erosion Control Plan

See Attachment	52		Le	gend
				Property Line
		9		Area of Land Disturbance
				Temporary Diversion
				Existing Drainage
				Finished Drainage
				Limits of Grading
				Silt Fence
				Gravel Exit
				Vegetation Specification
				Tree Preservation
				Stockpiled Soil
				orth Arrow
* Land disturbance includes areas of soil disturband driveways, staging, temporary access, on-site was	nce for any po stewater syste	urpose, including fou ems, and on- and off-	ndations, footir site utilities.	igs, parking,
Project Location:	,	,		
(Address) (Street) (Lot) 761 W 2ND AVE				
Builder:Contractor	Owner: _	Chugach Electric Asso	ciation, Inc.	
Worksheet completed by: Annie Collie, Midnight S	Sun Environme	ntal, LLC		
Installation and maintenance of erosion control pr	ractices respo	onsibility of:		
Name:Contractor, TBD	Phone:		**	
Permanent seeding/sodding responsibility of:				ŭ
Name: N/A	Phone:	N/A		

Page 5 of 6

Type 1 Storm Water Pollution Prevention Plan

OWNER'S STATEMENT


I have read the above checklist, completed this form, completed and attached the *Stormwater Runoff Threat Assessment Form*, and have enclosed the necessary design information concerning the above referenced proposed project demonstrating it is a Type 1 SWPPP Project. By my signature I certify the enclosed information, that I will install or perform necessary BMPs and maintain them throughout the project, and that the project is (check one):

the project is (check one):	e the project, and that
_x privately owned and that I am the owner privately owned and t	hat I am the developer.
I further certify that the project is or is not part of a larger common plan of the project is part of a common plan of development that collectively disturbs 1 or the NOI.	
Marty Freewau	2023-03-22
Signature (please sign in ink):	Date:
Name and Official Title (print or type):	
Marty Freeman	
Company or Agency (if applicable): Chugach Electric Association, LLC	

Page 6 of 6

Stormwater Threat Assessment Form

Please circle your responses.



STORM WATER REVIEW REQUEST

Work Order No.	Project Title	Project Status	Manager	Designer	
E2114030	Depot Dr AK Railroad Relo-SOA	Active	Brad Jackson	Moritz Salvanera	


Grid Number(s) 1229E			9B, 1230A		Le	gal Description		N/A	
Wet Areas on Project Work in Wet		Trench Dewatering		MOA Wetlands Maps		Dire-	ction		
Nearest Water Body		Clearing Length/Width							
Nearest Well		Trench L/\	N/Depth 48" min depth / 60" min. below railroad tracks						
Equipment			Added	Added			Removed		
Poles		various							
Pad Xfmrs		various							
Switch Cabs.		SC 1186,1187							
Vaults		various							
Proposed Construction Methods									
Comments									
Please perform SWPPP review.									

Site Drawing


A separate storm water site drawing will be developed for each project. To ensure accuracy, include the following information:

- Proposed location(s) of clearing
- · Proposed location(s) of trenching
- Proposed location(s) of new equipment
- Location(s) of retired equipment
- Proposed location(s) of direction drilling with pit locations
- Location(s) of drainage features, storm water inlets, and wetlands
- Proposed location(s) of stockpiles or spoil piles
- Proposed location(s) of asphalt / concrete cuts

E2114030 Project Location



March 11, 2023



Maxar, Microsoft, MOA Watershed Management, Kenai Peninsula Borough, Matanuska-Susitna Borough GIS, Municipality of Anchorage, State of Alaska,

U.S. Fish and Wildlife Service **National Wetlands Inventory**

E2114030 NWI Map



March 13, 2023

Wetlands

Estuarine and Marine Deepwater

Estuarine and Marine Wetland

Freshwater Emergent Wetland

Lake


Freshwater Forested/Shrub Wetland


Other

Freshwater Pond

Riverine

This map is for general reference only. The US Fish and Wildlife Service is not responsible for the accuracy or currentness of the base data shown on this map. All wetlands related data should be used in accordance with the layer metadata found on the Wetlands Mapper web site.





Signature Certificate

Reference number: 7WMEC-3AROS-ZLQA5-73AEZ

Signer Timestamp Signature

Marty Freeman

Email: marty_freeman@chugachelectric.com

 Sent:
 21 Mar 2023 16:44:57 UTC

 Viewed:
 22 Mar 2023 16:44:51 UTC

 Signed:
 22 Mar 2023 16:45:17 UTC

Recipient Verification:

✓ Email verified 22 Mar 2023 16:44:51 UTC

Marty Freewau

IP address: 192.189.218.190 Location: Anchorage, United States

Document completed by all parties on:

22 Mar 2023 16:45:17 UTC

Page 1 of 1



Signed with PandaDoc

PandaDoc is a document workflow and certified eSignature solution trusted by 40,000+ companies worldwide.

